


RENTAL **TCR-6000/2** AIR HOIST

The **TCR-6000/2** is a 6 tonne chain hoist from Red Rooster Lifting. This is part of our air hoist hook suspension range for lifting equipment applications in industry.



**RED ROOSTER
LIFTING**

RAISING EXPECTATIONS



The **Red Rooster Lifting** TCR series of air hoists offers a comprehensive range of lifting equipment suited to all types of industrial and marine environments. Red Rooster Lifting hoists are the perfect lifting solution for where the duty is high, or where a robust hoist is required to withstand harsh conditions.

STANDARD FEATURES

- Toku rotary vane motor
- Robust epicycle gearbox
- Failsafe automatic internal disc brake
- Mechanical upper & lower switches
- Cast steel housing
- Internal silencing down to 83 dB(A)
- Alloy safety swivel hooks with safety catch
- Load chain 11.2 x 34mm of European manufacture to EN818-7
- Automatic load limiter

AVAILABLE OPTIONS

- ATEX zone 1 & 2 specification
- Chain collector

T: +44 (0) 1651 872101
sales@redroosterlifting.com

REDROOSTERLIFTING.COM

Red Rooster Lifting Limited Nauta House, The Meadows, Oldmeldrum, Inverurie, Aberdeenshire, UK, AB51 0EZ

RENTAL TCR-6000/2 AIR HOIST




**RED ROOSTER
LIFTING**

RAISING EXPECTATIONS

DIMENSIONS

All measurements are in mm
Information subject to change without notice



HOIST MODEL	TCR-6000/2
WLL	6000 kg
CHAIN FALLS	2
LIFTING SPEED WITH LOAD	1.4 m/min
LIFTING SPEED WITHOUT LOAD	2.9 m/min
LOWERING SPEED WITH LOAD	2.3 m/min
AIR CONSUMPTION LIFTING	33 l/sec
AIR CONSUMPTION LOWERING	43 l/sec
WORKING PRESSURE	6 Bar
AIR CONNECTION	1/2" BSP
MINIMUM HOSE DIA.	3/4"*
WEIGHT 3M HOL	91 kg
ADDITIONAL METRE HOL	5.4 kg

*For air supply hose lengths in excess of 10 metres, hose I.D. should be increased

T: +44 (0) 1651 872101
sales@redroosterlifting.com